

**(12) UK Patent Application (19) GB (11) 2 285 165 (13) A**

(43) Date of A Publication 28.06.1995

(21) Application No 9425465.3

(22) Date of Filing 16.12.1994

(30) Priority Data

(31) 05318780 (32) 17.12.1993 (33) JP

(71) Applicant(s)

International Business Machines Corporation

(Incorporated in USA - New York)

Armonk, New York 10504, United States of America

(51) INT CL<sup>6</sup>

G11B 20/12 20/18

(52) UK CL (Edition N )

G5R RB26 RB784

(56) Documents Cited

EP 0522750 A2

(58) Field of Search

UK CL (Edition N ) G5R RB26 RHE RHX

INT CL<sup>6</sup> G11B 5/012 5/55 7/007 20/12 20/18 27/10

ONLINE DATABASES: WPI,INSPEC

(72) Inventor(s)

Takashi Nakamura

Tsutomu Numata

Kenji Ogasawara

Yuji Kigami

Koji Kurachi

Mayumi Okada

Takao Matsui

Yuji Yokoe

(74) Agent and/or Address for Service

J P Richards

IBM United Kingdom Patent Operations,

Hursley Park, Winchester, Hants, SO21 2JN,

United Kingdom

**(54) A disk sector format which eliminates the need for sector identifiers**

(57) A disk drive apparatus comprising a disk recording medium in which each track is divided into a servo area which stores information for identifying the track position and a plurality of data sectors wherein at least one of said data sectors crosses said servo area and a look-up table is provided for identifying the position of each sector based upon the relationship between a physical sector identifier, said position information and the capacity of the sector crossing said servo area.

When a signal SP at the end of a servo area is detected in a dead state 80 during start up, a first data state 84 for the start of a sector transits to a second data state 86 for the later region of the sector being divided in accordance with the capacity stored in a current sector's pointer register 60. At the beginning of the sector, the contents of a next sector's pointer register 62 is stored in register 60 and the contents of a next sector's operation register 66 is stored in a current sector's operation register 64. Upon completion of sector processing, the first data state 84 is maintained when the next sector is contiguous. When a terminate instruction is stored in register 64, the process moves to dead state 80. When the servo area arrives, the process moves to idle state 82. Responsive to this state, the magnetic head is activated to enable read and write operation 5 for sectors having no sector ID on the disk.




FIG. 5

GB 2 285 165 A

1 / 13





FIG. 1

2 / 13

FIG. 2




FIG. 3

D\_LST 03, 07, 07, 12, 12, 12, ...

FIG. 4

5 / 13




FIG. 5

6/13





FIG. 6

7/13

FIG. 7



8/13




FIG. 8




FIG. 9






FIG. 10

10/13

FIG. 11

11/13



**FIG. 12**






FIG. 13


13 / 13



**FIG. 14**



**FIG. 15**



**FIG. 16**

**2285165**

JA9-93-048/jpr

1

**INFORMATION RECORDING DISK AND DISK DRIVE SYSTEM**

This invention relates to information recording disks and disk drive systems, and more specifically to information recording disks used in information recording devices such as data-recording hard disk drive unit and disk drive systems using such information recording disks.

As information recording media for recording a greater amount of information used in computers or other machines, hard disk drive units (hereinafter referred to as HDD devices) have been implemented. The HDD device is provided with a number of magnetic recording disks (referred to as disks) and writes information in or reads it from its disk by positioning a read/write head onto a desired track defined on the disk.

Typically the disk in the HDD device is provided with a plurality of tracks, each of which being divided by data sectors (referred to as sectors) which are 128, 256, or 512 bytes. A divided sector is usually given an identifier of itself, i.e., so-called sector ID, in which a serial number of the sector, sector type, and sector identifying information such as DEFECT information indicating a bad sector originated from manufacturing. In a conventional HDD device, read and write operation is performed while the sector ID is referenced to determine whether the sector is a target or not.

The physical location of the sector can be determined by the face number of the disk (HEAD number), cylinder number (CYL number), and sector number (SCT number). The HEAD number and CYL number can be determined as seek operation is ended. The SCT number can be determined by reading information previously recorded on the disk, such as the servo area, or by counting from the beginning sector, since the SCT number changes with the rotation of the disk.

It is necessary for reading or writing information to perform operations for every sector, such as converting a logical sector into a physical sector and identifying a location on the disk where a corresponding sector belongs. This requires many types of information to be stored in the sector ID. Therefore the ID region has been made larger so as to prevent erroneous sector identifying information from being recorded as prerequisite sector identifying information is too large to be recorded. Then, an area for controlling the HDD device for each sector, i.e., an ID area of sector identifying information has been affixed, thus

JA9-93-048/jpr

2

necessitating reduction of the area where information can be recorded and which is originally provided in the HDD device by using the ID area.

5 To overcome this problem, there has been suggested an information recording disk whose sectors are so formatted that the ID area is not required for recording information (see JA5-174498).

10 Even with an information recording disk where the conventional ID area is not provided for each sector, however, a position identifying area such as a servo area is still needed to identify positions on the disk of the HDD device. Then a single sector can be divided by the servo area. The HDD device using an information recording disk whose ID area is not provided for every sector could recognize a single sector as multiple or assume that a corresponding sector is ended even when it is actually not  
15 but continuous.

With aforementioned facts considered, the position invention is intended to provide an information recording disk capable of storing more information and readily reading information. It is another purpose of the  
20 present invention to provide a disk drive system which is capable of readily and rapidly reading and writing a greater amount of information.

In order to accomplish these and other objects of the invention, the information recording disk according to claim 1 includes at least one  
25 servo area wherein position information is stored for identifying the track position; at least one track wherein an area without said servo area is divided by a plurality of sectors of identical capacity including at least one sector crossing said servo area; and a table representing, for uniquely determining the position of each of a plurality of sectors,  
30 the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing said servo area up to the crossing position.

35 The information recording disk according to claim 2 of the invention includes at least one servo area wherein position information is stored for identifying the track position; at least one track wherein an area excluding said servo area is divided by a plurality of sectors having the same capacity and including at least one sector which crosses said servo  
40 area; a table representing, for uniquely determining the position of each of a plurality of sectors, the relationship among a physical sector



JA9-93-048/jpr

3

identifier for identifying each sector on said divided track based on said servo area, said position information, the capacity of the sector crossing said servo area up to the crossing position; and list storage means for sequentially storing as a pseudo logical sector identifier a logical sector identifier which should be given to a bad sector when sequentially specifying a logical sector identifier for identifying each sector other than the bad sector included in said track.

The disk drive system according to claim 3 of the invention comprises an information recording disk having at least one track divided by at least one servo area wherein position information is stored for identifying the track position so that an area without said servo area has contiguous sectors having the same capacities; a magnetic head for reading and writing information in said information recording disk; storage means consisting of a first storage means for storing the structure of a current sector, a second storage means for storing the structure of the next sector, a third storage means for storing the operation of the current sector, and a fourth storage means for storing the operation of the next sector; a table which stores the structure of each sector for representing the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing said servo area up to the crossing position, in order to uniquely determining the position of each of a plurality of sectors; list storage means which sequentially stores as a pseudo logical sector identifier a logical sector identifier to be given to a bad sector when sequentially specifying a logical sector identifier for identifying each sector other than the bad sector included in said track; calculating means for referencing said list storage means to read the number of logical sector position identifiers which is equal or smaller than requested logical sector position identifiers and adding the number being read to requested logical sector position identifiers to calculate physical sector position identifiers for physical sectors which correspond to requested logical sector identifiers; processing means for taking actions for corresponding sectors in accordance with the structure of the current sector stored in said first storage means and the operation of the current sector stored in said third storage means; means for determining the beginning of a sector based on the structure of the current sector stored in said first storage means after identifying the end of said servo area with an output signal from said magnetic head; and control means for exercising control so that, when said beginning of a sector is determined, the first storage

JA9-93-048/jpr

4

means stores the structure of the next sector stored in the second storage means and the third storage means stores the operation of the next sector stored in the fourth storage means, and during processing by said processing means, for referencing said table to have the second storage means store the structure of the next sector including the physical sector position identifier calculated by said calculating means and to have the fourth storage means store the operation of the next sector.

The disk drive system according to claim 4 of the invention comprises the information recording disk according to claim 2; a magnetic head for reading and writing information in said information recording disk; storage means consisting of a first storage means for storing the structure of a current sector, a second storage means for storing the structure of the next sector, a third storage means for storing the operation of the current sector, and a fourth storage means for storing the operation of the next sector; calculating means referencing said list storage means for reading the number of logical sector position identifiers which is equal to or larger than requested logical sector position identifiers and adding the number being read to the requested logical sector position identifiers to calculate a physical sector position identifier for a physical sector corresponding to the requested logical sector identifiers; processing means for taking actions for a corresponding sector in accordance with the structure of the current sector stored in said first storage means and the operation of the current sector stored in the third storage means; means for determining the beginning of a sector based of the structure of the current sector stored in said first storage means after identifying the end of said servo area with an output signal from said magnetic head; and control means for exercising control, when said beginning of the sector is determined, to have the first storage means store the structure of the next sector stored in the second storage means and have the third storage means store the operation of the next sector stored in the fourth storage means and further to reference said table during processing by said processing means to have the second storage means store the structure of the next sector including the physical sector position identifier calculated by said physical sector position calculating means and have the fourth storage means store the operation of the next sector.

The disk drive system according to claim 5 of the invention comprises the information recording disk according to claim 1; a magnetic head for

JA9-93-048/jpr

5

reading and writing information in said information recording disk;  
means, assuming a virtual sector and virtual track which have a  
predetermined capacity, for creating a bad sector table consisting of a  
virtual sector table wherein a physical sector identifier to be given to  
the position of a bad sector is sequentially stored as a pseudo logical  
sector identifier and a virtual track table for storing the pseudo  
logical sector identifier for the bad sector corresponding to the  
smallest physical sector identifier for the same track which is included  
in said virtual sector table, when sequentially specifying the physical  
sector identifier indicating the position of each sector other than the  
bad sector included in said track; means for creating a virtual ID table  
representing the structure of each sector in a virtual track which  
consists of the physical sector identifier for identifying each sector on  
said divided track based on said servo area, said position information,  
the capacity of the sector crossing said servo area up to the crossing  
position, and the logical sector identifier, using said table and said  
bad sector table; and control means for referencing said virtual ID table  
to determine a virtual track and virtual sector which correspond to the  
position identifier of a requested logical sector and determining a  
physical sector corresponding to the determined virtual track and virtual  
sector to process for the determined sector.

The disk drive system according to claim 6 is characterized in that said  
magnetic head comprises, in the disk drive system according to any one  
claim of claims 3 to 5, a recording portion for recording information in  
said information recording disk and a reading portion spaced apart by a  
determined amount from said recording portion for reading information  
from said information recording disk, the length of the head gap of said  
reading portion being substantially equal to the length of the head gap  
of said recording portion.

The disk drive system according to claim 7 is characterized in that said  
magnetic head comprises, in the disk drive system according to any one  
claim in claims 3 to 5, a recording portion for recording information in  
said information recording disk and a reading portion spaced apart by a  
predetermined amount from said recording portion for reading information  
from said information recording disk, the length of the head gap of said  
reading portion being substantially equal to the width of said track.

The information recording disk according to claim 1 of the invention  
includes at least one servo area. This servo area stores position

JA9-93-048/jpr

6

information for identifying the track position by means of, for instance, a servo pattern, thus allowing a sequence of track positions or multiple servo areas on the same track. An area without the servo area has at least one track. This track is divided by a plurality of sectors having the same capacities. At least one of such tracks includes a sector crossing the servo area. To uniquely determining the position of each of a plurality of sectors, the information recording disk includes a table representing the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing said servo area up to the crossing position. Using this information recording disk eliminates the need for recording a sector ID for every sector, thus increasing the amount of information which can be recorded on the information recording disk. In addition, since the relationship between the physical sector identifier and the capacity up to a position where the servo area is crossed is stored in the table, the target sector can be readily searched even when there is a sector crossing the servo area.

The information recording disk according to claim 2 further includes in said information recording disk list storage means for sequentially storing as a pseudo logical sector identifier a logical sector identifier to be affixed to a bad sector when sequentially specifying the logical sector identifier for identifying each sector other than the bad sector included in the track. Thus the pseudo logical sector identifier is stored in the bad sector, and even when a read or write request indicates a logical sector, a corresponding physical sector can be readily searched by simple processing such as adding a stored number of pseudo logical sector identifiers to the requested logical sector identifier.

The disk drive system according to claim 3 of the invention, uses an information recording disk having at least one track which is divided by at least one servo area storing position information for identifying the track position so that an area excluding said servo area is divided to have contiguous sectors having the same capacities. Information is read or written in the information recording disk by a magnetic head. To uniquely determine the position of each of a plurality of sectors, a table of the structure of each sector is stored which represents the relationship among a physical sector identifier for identifying each sector on said divided track based on the servo area, the position information, and the capacity of the sector crossing the servo area up to the crossing position. Furthermore, a list storage means is used to

JA9-93-048/jpr

7

sequentially store a logical sector identifier to be affixed to a bad sector as a pseudo logical sector identifier when sequentially specifying the logical sector identifier for identifying each sector other than the bad sector contained in the track. Therefore, the physical sector position calculating means can calculate the physical sector position identifier for a physical sector which corresponds to a logical sector identifier being requested from, for instance, a host computer by referencing the list storage means and adding to the requested logical sector position identifiers the number of logical sector position identifiers which is equal to or smaller than the requested logical sector position identifiers.

As described in claim 4, by using the information recording disk according to claim 2, this table and list storage means can be read from the information recording disk.

Since the sector ID is not recorded on the information recording disk, the disk drive system is provided with storage means configured with a number of storage elements such as registers for storing the structure and operation of the current sector. This storage means comprises a first storage means for storing the structure of the current sector, a second storage means for storing the structure of the next sector, a third storage means for storing operation of the current sector, and a fourth storage means for storing operation of the next sector. The sector determining means determines the beginning of a sector based on the structure of the current sector which is stored in the first storage means after identifying the end of the servo area by using, for instance, a servo sector pulse signal or output signal from the magnetic head. Thus, the first storage means has stored the structure of the current sector and whether the remaining portion of the current sector remains at the end of the servo area can be determined. When the remaining portion of the current sector remains there, the beginning of the next sector begins after the remaining capacity is passed. When it does not remain, the beginning of the next sector starts immediately after the end of the servo area. When the beginning of the sector is determined, the control means exercises control so that the first storage means stores the structure of the next sector which is stored in the second storage means and the third storage means stores operation of the next sector which is stored in the fourth storage means. Consequently the storage means has stored the structure and operation of the sector at its beginning as those of the current sector. During processing by the processing means,

JA9-93-048/jpr

8

since the structure and operation of the next sector can be updated in the second and fourth storage means, control is exercised by referencing the table so that the second storage means stores the structure of the next sector which includes the physical sector position identifier  
 5 calculated by the physical sector position calculating means and the fourth storage means stores operation of the next sector. Therefore, the structure and operation of the next sector can be stored in the second and fourth storage means before processing for the current sector is completed. The processing means performs processing, e.g. reading and  
 10 writing information, for the corresponding sector in accordance with the structure of the current sector which is stored in the first storage means and operation of the current sector which is stored in the third storage means.

15 The disk drive system according to claim 5 of the invention reads and write information in the information recording disk according to claim 1 by using a magnetic head. Therefore the table can be read from the information recording disk. The bad sector table creating means assumes a virtual sector and virtual track which have a predetermined amount of  
 20 capacity, respectively, and when sequentially specifying the physical sector identifier indicating the position of each sector other than the bad sector included in the track as a logical sector identifier, creates a bad sector table consisting of a virtual sector table storing sequentially the physical sector identifier to be provided for the  
 25 position of the bad sector as a pseudo logical sector identifier and a virtual track table for storing the pseudo logical sector identifier for the bad sector which corresponding to the smallest physical sector identifier on the same track which is contained in said virtual sector table. Using this table and the bad sector table, the virtual ID table  
 30 creating means creates a virtual ID table for representing the structure of each virtual sector on the virtual track wherein each structure corresponds to the sector ID, said table consisting of a physical sector identifier for identifying each sector on said divided track based on the servo area, position information, the capacity of the sector crossing the  
 35 servo area up to the crossing position, and a logical sector identifier. The control means references the virtual ID table to determine a virtual track and virtual sector which correspond to a requested logical sector position identifier and determines a corresponding physical sector in the determined virtual track and virtual sector to exercise control for  
 40 processing on the determined sector.

JA9-93-048/jpr

9

The magnetic head comprises a recording portion for recording information in the information recording disk and a reading portion spaced apart by a specified amount from said recording portion for reading information from the information recording disk, as claimed in claim 6. The length of the head gap of the reading portion can be configured so as to approximately conform to the length of the head gap of the recording portion. This will improve the density of the track width which corresponds to the information recording density in the radial direction of the disk.

Alternately, as described in claim 7, a magnetic head may be used which is so configured that the length of the head gap of the reading portion substantially conforms to the track width. This will also improve the density of the track width which corresponds to the recording density in the radial direction of the disk.

Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a schematic block diagram illustrating the structure of an HDD device to which the invention is applicable.

Fig. 2 shows an image of zones on the disk of the HDD device.

Fig. 3 shows an image of formatted zones on the disk.

Fig. 4 is a schematic diagram illustrating an example of a track including bad sectors.

Fig. 5 is a block diagram illustrating the structure of the HDC of the HDD device to which the invention is applicable.

Fig. 6 is a flow chart illustrating the steps for deducing the physical position of sectors relative to the first embodiment.

Fig. 7 is a flow chart illustrating the steps for sector recognition and structure determination relative to the first embodiment.

Fig. 8 shows an image of state transitions of a state controller in a construction of sectors in a predetermined track in predetermined zone Zn.

Fig. 9 shows an image of state transitions of the state controller.

JA9-93-048/jpr

10

Fig. 10 is a conceptual diagram illustrating the structure of a virtual sector table and virtual track table relative to the second embodiment.

5 Fig. 11 is a flow chart illustrating the creation of a virtual ID table relative to the second embodiment.

Fig. 12 is a flow chart illustrating read and write operation for information using the virtual ID table relative to the second embodiment.

10 Fig. 13(a) is a schematic diagram illustrating the recording state of information in the disk of the prior art HDD device and Fig. 13(b) is a schematic diagram illustrating the recording state of information in the disk of the HDD device to which the invention is applicable.

15 Fig. 14 is a conceptual diagram illustrating the positions of an MR element during write and read operation in a prior art HDD device.

Fig. 15 shows the relation between the amount of off-track and read error.

Fig. 16 shows an image of an information-recorded state in a servo area.

20

Referring to the drawings, embodiments of the present invention will now be described in greater detail. The first embodiment applies the invention to HDD device 10 employing a multiple-zone technique wherein a magnetic recording disk (hereinafter simply referred to as disk) is divided in the radial direction into a predetermined number of areas (referred to as zones) and a sector servo mechanism is used to perform write and read operation from the inner to the outer circle of the disk at a predetermined line density.

25

30 Fig. 1 shows HDD device 10 related to the first embodiment. HDD device 10 is equipped with drive 14 for rotating shaft 12 in a high speed. Attached to shaft 12 is cylindrical support 16 so that both axes coincide. On the outer periphery of support 16 a number of (two in Fig. 1) disks 18A and 18B are attached with a predetermined space from each other. Disks 18A and 18B are formed to have predetermined thicknesses, each of which is made of a hard material with a magnetic material applied to both surfaces to use them as recording surfaces. In the center of disks 18A and 18B, a hole is provided which has approximately the same diameter as the outer dimension of support 16, which is inserted into  
40 this hole. Disks 18A and 18B are fixed at the outer periphery of support

35



JA9-93-048/jpr

11

16. Therefore, when shaft 12 is rotated by drive 14, disks 18A and 18B are rotated integrally with support 16.

On each recording surface of disk 18A and 18B, as shown in Fig. 2, a plurality of servo areas 50 are formed radially in the radial direction of disk 18, with remaining area formed as track region 52. In servo areas 50, a servo signal (see Fig. 16), e.g. burst pattern, for indicating the direction of data track arrangement, for instance, is recorded. Corresponding to data tracks, a special code (e.g. area of approximately 1 usec where no signal is present) indicating the beginning of a pattern and a gray code (cyclic binary code) indicating for example the address of each data track are recorded. In the end portion in the direction of rotation of servo area 50, there is recorded information for generating sector pulse signal SP indicating the end of servo area 50 (i.e. beginning of a sector). In data track area 52, a number of data tracks are formed concentrically with pitch P along the radial direction, and information is written in each data track in the rotation direction of disk 18 by a magnetic head described below.

HDD device 10 is provided with magnetic heads 20A to 20D having predetermined gap widths and lengths which correspond to recording surfaces of disks 18A and 18B. Each of magnetic heads 20A to 20D is configured with an MR element which includes a read element (not shown) for reading information and a write element (not shown) for writing information. Magnetic heads 20 A to 20 D are attached to the end portion of access arms 22 A to 22 D, respectively, and retained slightly above (e.g. approximately 0.1 to 0.2 micron) corresponding recording surfaces of disks 18A to 18B. Each rear end of access arms 22A to 22D is attached to support 24, which is in turn attached to drive 28 via shaft 26. Rotation of drive 28 by a predetermined angle will rotate access arms 22A to 22D. This rotation of access arms 22A to 22H causes each of magnetic heads 20A to 20D to move toward the radial direction on each recording surface of disks 18A and 18B.

Drive 28 is connected to a hard disk controller (referred to as HDC) 30, to which the read and write elements (not shown) of magnetic heads 20A to 20D are also connected.

This embodiment defines as a logical block address (or LBA) the number of a sector to be specified when a read/write request is issued by other devices such as host computers. Also defined as an absolute block address

JA9-93-048/jpr

12

(or ABA) is the number assigned sequentially in the order of sectors, for all sectors including bad sectors, such as defectives. In the following description, it is assumed a single sector is formatted with a storage capacity of 512 bytes.

5

As shown in Fig. 2, each of disks 18A and 18B is divided into zones Z0, Z1, Z2, ..., Zn, where n is a predetermined number, and each zone has previously specified information, such as position information. For example, during manufacturing, zone Z0 has a reserved area ranging from a minimum absolute block address (or MIN\_ABA) 0 to a maximum absolute block address (or MAX\_ABA) 102399 and cylinders ranging from a minimum cylinder number (or MIN\_CYL) 0 to an end cylinder number (END\_CYL) 199, and is formatted so that the number of sectors per track (SCT\_TRK) is 128 and the number of sectors per cylinder (SCT\_CYL) is 512. Zone Z1 and later

10

15

have a similar configuration, which is shown in Table 1 below. Information associated with each zone shown in this table is previously recorded in place on the disk. By referencing this zone table 32, it is possible to determine from which zone a specified sector starts.

Table 1

20

ZONE TABLE

25

#ZONE	MIN_ABA	MAX_ABA	SCT_TRK	SCT_CYL	MIN_CYL	END_CYL
Z 0	0	102399	128	512	0	199
Z 1	102400	191999	112	448	200	399
Z 2	192000	345599	96	384	400	799
Z 3	345600	473599	80	320	800	1199
.	.	.	.	.	.	.
.	.	.	.	.	.	.

30

35

40

In the present embodiment, since write or read operation is performed over the disk from the innermost to outermost circle with a predetermined line density, each zone will have a different storage capacity on disks 18A and 18B by rotation of an identical angle. That is, as shown in Fig. 3(a), when zone Z0 has an information storage of the whole capacity of two sectors (512 x 2 bytes) in data track area 52 between servo areas 50, zone Z1, as shown in Fig. 3(b), has an information storage of two-sector capacity (512 + 384 bytes), zone Z2 has an information storage of two-sector contents (512 + 256 bytes), as shown in Fig. 3(c), and zone Z3 has a two-sector capacity (512 + 128 bytes). Thus the storage capacity decreases as the disk track reaches the innermost circle. Along with this, a single sector can be divided.

JA9-93-048/jpr

13

In view of the above, in the embodiment, there is previously determined the relationship among a physical sector number (DT\_SCT), servo number (SV\_SCT), sector capacity up to a position where the sector is divided by servo area 50 (PTR), and information indicating whether a servo area is present between this sector and the next sector (LAST) for the sector in each zone. This relationship is indicated as pointer table 34 and shown in Tables 1 to 5 for examples of zones Z0, Z1, Z2, and Z3. Also other pointer tables 34 for zone Z4 and later are specified at the time of fabrication. Pointer tables 34 for each zone, as shown in Tables 2 to 5 are previously recorded at predetermined positions.

Table 2

## POINTER TABLE (ZONE #0)

DT_SCT	#0	#1	#2	#3	#4	#5	. . .	#127
SV_SCT	#0	#0	#1	#1	#2	#2	. . .	#63
PTR	200H	200H	200H	200H	200H	200H	. . .	200H
LAST	0	0	0	0	0	1		1

Table 3

## POINTER TABLE (ZONE #1)

DT_SCT	#0	#1	#2	#3	#4	#5	#6	. . .	#111
SV_SCT	#0	#0	#1	#1	#2	#2	#3	. . .	#63
PTR	180H	200H	100H	200H	080H	200H	. . .	200H	
LAST	0	0	0	0	0	0	1		1

Table 4

## POINTER TABLE (ZONE #2)

DT_SCT	#0	#1	#2	#3	#4	#5	. . .	#95
SV_SCT	#0	#0	#1	#2	#2	#3	. . .	#63
PTR	200H	100H	200H	200H	100H	200H	. . .	200H
LAST	0	0	1	0	0	1		1

JA9-93-048/jpr

14

Table 5

## POINTER TABLE (ZONE #3)

	DT_SCT	#0	#1	#2	#3	#4	. . .	#79
	SV_SCT	#0	#0	#1	#2	#3	. . .	#63
5	PTR	200H	080H	100H	180H	200H	. . .	200H
	LAST	0	0	0	0	1		1

Now bad sectors will be described. As shown in Fig. 4, when a block (sector) whose absolute block address ABA corresponds to 03, 08, 09, 15, 16, and 17 is defective, the logical block address skips this defective sector. For example, the logical block address whose absolute block address ABA corresponds to 04 is 03. For the skipped bad sector whose absolute block address ABA is 03, a value assumed to be assigned if it is not defective (03 in this example) is stored as value PLBA (PSUEDO LBA). All of stored values PLBA are sequentially stored as defect list D\_LST.

Thus, absolute block address ABA can be determined by adding the number of values PLBA listed in defect list D\_LST when logical block address LAB is specified. For example, when logical block address LBA = 7 is specified, the values of defect list D\_LST (three values of 03, 07, and 07 in this case) are added to obtain  $ABA = 7 + 3 = 10$ .

$$ABA = LBA + (\text{number of PLBAs which are equal to or smaller than LBA}) \dots (1)$$

As shown in Fig. 5, HDC30 has a local CPU (not shown) and includes registers, state controller 68, first data circuit 70, and second data circuit 72 described below. Registers include register 60 for storing the structure of a current sector (referred to as current sector's pointer register or CSPR), register 62 for storing the structure of the next sector (referred to as next sector's pointer register or NSPR), register 64 for storing operation of the current sector (current sector's operation register or CSOR), and register 66 for storing operation of the next sector (next sector's operation register or NSOR). These registers CSPR60, NSPR62, CSOR64, and NSOR66 are connected to local CPU (not shown) bus 74 so that data can be transferred to each other.

State controller 68 is a circuit for controlling the states in which HDC30 is operative. These states include dead state 80 where HDC30 operation is prevented due to, for instance, a non-recording area of disk sector, idle state 82 in which operation of HDC 30 is paused, first data

JA9-93-048/jpr

15

state 84 indicating the state of data contained in a single sector from its beginning to the end or servo area 50, and second data state 86 indicating the state of data in the later area of a single sector being divided by servo area 50. This state controller 68 is connected to registers CSPR60 and CSOR64 and also connected to first data circuit 70 and second data circuit 72 which are provided for temporarily retaining data.

Referring now to figures, operation of HDD device 10 according to the present invention will be described. As noted above, HDD device 10 of the invention has disks without the sector ID recorded per sector. First deduction of the physical position of target sectors will be described with reference to the flow chart shown in Fig. 6. A host device specifies a logical block address LBA which is a sector number to HDC30 along with a data write or read request (step 102). HDC30 references the defect list D\_LST described above, and using equation (1), calculates an absolute block address ABA for all sectors including bad sectors which corresponds to the specified logic block address LBA at step 104. For example, in Fig. 4, when logical block address LBA07 is specified, absolute block address ABA = 10 is calculated. Next HDC30 references zone table 32 (Table 1) to determine zone Zn where the calculated absolute block address ABA belongs (step 106). Then a physical position in determined zone Zn is deduced as follows (step 108).

Assuming the host device requests for reading sectors from #L to #M for a logical block address LBA. Then a corresponding absolute block address ABA is calculated as #N and zone Zn it belongs is determined as #Z. Furthermore, it is assumed that the first absolute block address ABA is MIN\_ABA (#Z) and the first cylinder is MIN\_CYL (#Z). In this case, an absolute block address ABA (#N) can be represented in the following equation (2).

$$\#N = \#ZN + \text{MIN\_ABA}(\#Z) \dots (2)$$

where #ZN is the sector serial number in zone #Z which corresponds to #L of logical block address LBA.

The sector serial number #ZN can be represented in the following equation (3).

$$\begin{aligned} \#ZN = \#S \\ + (\text{SCT\_TRK}(\#Z) \cdot \#HD) \\ + (\text{SCT\_CYL}(\#Z) \cdot \#ZCYL) \dots (3) \end{aligned}$$

JA9-93-048/jpr

16

where SCT\_TRK (#Z) is the number of sectors per track in zone #Z and SCT\_CYL (#Z) is the number of sectors per cylinder in zone #Z.

5 Therefore, for determining the absolute block address ABA (#N), the surface number (HD number), cylinder number (CYL number), and sector number (SCT number) of a magnetic disk will be as follows:

CYL number = #CYL = #MIN\_CYL (#Z) + #ZCYL

HD number = #HD

10 SCT number = #S

Based on a physical position calculated as above, seek operation is performed by switching and moving the head to a target cylinder (step 110).

15

Next, sector recognition/structure determination will be described with reference to Fig. 7.

20 When a sector pulse signal SP indicating that servo area 50 is ended is input at step 202, current sector's pointer register CSPR60 is read at step 204, and it is determined at step 206 whether sector capacity PTR up to a position where the current sector is divided by servo area 50 is 0 or not.

25 If the decision is positive, i.e. no division occurs, then the contents of next sector's pointer register NSPR62 is stored in CSPR60 at step 210, sector processing such as read and write is performed immediately after the sector pulse signal SP at step 212. On the other hand, if the decision is negative, the later section of the divided sector immediately follows the sector pulse signal SP. Then after the capacity indicated by the sector capacity PTR is passed (step 208), the contents of NSPR62 is stored in CSPR60 (step 214), and sector processing after sector capacity PTR being passed follows (step 216).

35 When processing is not completed for all sectors at step 218, it is determined whether information LAST indicating the presence or absence of servo area 50 between the current sector and next sector is 0 or not (step 220). If the answer is positive, i.e. LAST = 0, then there exists another sector immediately after the current sector. The contents of NSPR62 is then stored in CSPR60 at step 222, and sector processing is performed immediately after sector pulse signal SP at step 224. Then

40

JA9-93-048/jpr

17

step 218 is returned to perform the above processing until all sectors are covered. On the other hand, if the answer is negative, i.e. LAST =/ 0, then another sector is absent in the current servo sector. The process returns to step 202, where sector pulse signal SP is waited for processing the next sector.

During processing for read or write operation (steps 212, 216, and 222), since the contents of NSPR62 is stored in CSPR60, NSPR62 can be updated. Then the local CPU references pointer table 34 at a predetermined time during said processing to store information on the next structure in NSPR62.

In this manner, the sector position can be recognized only with sector pulse signal SP even if no sector ID exists on the disk.

Said processing for read or write operation, i.e. operation on sectors includes reading from sectors (READ), writing in sectors (WRITE), passing through a corresponding sector (SKIP), and temporary halt of processing (STOP), which are processed by referencing current sector's operation register CSOR64. Similarly as sector recognition/structure determination described above, next sector's operation register NSOR66 can be specified during processing of the current sector. Thus, at the beginning of each sector, the contents of NSOR66 is stored in CSOR64 and thereafter it is possible to update the contents of NSOR66. Therefore, during processing of the current sector, NSOR66 can be specified.

Said sector recognition and structure determination as well as operation on sectors will now be further described with reference to Figs. 8 and 9.

Fig. shows an image of the sector structure on a predetermined track in predetermined zone Zn and transition of the state of state controller 68. During start up of HDC30, state controller 68 is in dead state 80. It changes to idle state 82 when HDC30 initiates control (see arrow S1 in Fig. 9), and remains in this state until the sector pulse signal SP is detected. Upon detection of sector pulse signal SP, based on sector capacity PTR (up to a position where the current sector is divided by servo area 50) stored in CSPR60, state controller 68 moves to first data state 84 or second data state 86. That is, since PTR = 0 indicates that the sector to be read or written is in its beginning, state controller 68 moves to first data state 84 (see arrow S2 in Fig. 9). On the other hand, if PTR =/ 0, state controller 68 moves to second data state 86

JA9-93-048/jpr

18

since the later portion of the sector is present which is divided by servo area 50 (see arrow S3 in Fig. 9).

5 If HDC30 is in first data state 84 and sector capacity PTR  $\neq$  0, then the current sector is divided. Therefore, state controller 68 receives halt signal S11 from first data circuit 70 (see Fig. 5) after operation on the former portion is completed, and then moves to idle state 82 (see arrow S4 in Fig. 9). At this time, if information LAST = 1, end signal S12 is inputted from first data circuit 70 in state controller 68 (see Fig. 5) 10 after operation on one sector is completed, then idle state 82 is entered.

If processing for a single sector is completed and information LAST = 0, then the next sector is contiguous, and first data state 84 is again entered (see arrow S5 in Fig. 9). At this time, if a stop data indicating 15 the end of processing by HDC 30 is stored in CSOR64, dead state 80 is entered (see arrow S6 in Fig. 9).

When HDC30 is in second data state 86 and information LAST = 0, the next sector follows the divided current sector. Then first data state 84 is 20 entered (see arrow S7 in Fig. 9) after operation on the second data is completed. When information LAST  $\neq$  0, servo area 50 follows the divided current sector. Thus, after operation on the second data is completed, idle state 82 is entered (see arrow S8 in Fig. 9). At this time, if the stop data indicating the end of processing by HDC 30 is stored in current 25 sector's operation register CSOR64, dead state 80 is entered (see arrow S9 in Fig. 9).

Operating the magnetic head in accordance with this state of HDC30 allows read and write operation to the sector which has no sector ID on the 30 disk. Repeating these steps allows read and write operation of all desired sectors.

The second embodiment will now be described in greater detail which uses a virtual ID table (VIT) which corresponds to the sector ID to accomplish 35 write and read operation to the disk without using the sector ID recorded on the disk. The second embodiment has similar configuration with the first embodiment, and identical numerals are used to designate identical elements.

40 To accomplish read and write operation to the disk without using the sector ID recorded on the disk, it is necessary to provide information



JA9-93-048/jpr

19

which corresponds to the sector ID. Virtual ID table (VIT) 38 according to the second embodiment covers all information provided as the prior art ID information, and as shown in Table 6 below, is a table combining pointer table 34 according to the first embodiment with logical block address LBA and information FLAG. For the values of logical block address LBA, the least significant bytes are used since there is no variation in higher bytes. Information FLAG is represented by one byte and configured with flag ETR\_FL (EOT FLAG) to be set if bit 0 is the last sector in a track, flag DEF\_FL (DEFECT FLAG) to be set if bit 1 is a bad sector, flag RES\_FL (REASSIGN FLAG) to be set if bit 2 corrupts after shipping to become unusable, and flag ETB\_FL (EOTBL FLAG) to be set if bit 7 is the last element of virtual ID table 38.

Table 6

Virtual ID table (VID)

DT_SCT	#0	#1	#2	#3	#4	#5	#6	. . .	#89
SV_SCT	#0	#0	#1	#1	#2	#2	#3	. . .	#59
PTR	00H	33H	80H	00H	33H	80H	00H	. . .	80H
LBA	55H	56H	FFH	00H	01H	FFH	02H	. . .	FFH
FLAG	00H	01H	02H	00H	00H	02H	04H	. . .	82H

Since servo area 50 on the disk permits servo number SV\_SCT to be detected, comparing this servo number SV\_SCT with servo number SV\_SCT on virtual ID table 38 allows detection of current physical sector number DT\_SCT (details described below).

Since no sector ID is recorded on the disk according to said embodiment, the format for formulating the disk is considered only for recording data over the entire surface of the disk. Any bad sector contained in this disk is recorded in a predetermined cylinder previously specified by defect list D\_LST.

In said embodiment, defect list D\_LST is referenced and equation (1) is used to calculate absolute block address ABA corresponding to a specified logical block address LBA (such as step 104). In the second embodiment, defect table 40 is used which is described below. This defect table 40 is created during formatting described above.

In this embodiment, a virtual track is assumed to have 10000H (65536) sectors, and the position of a bad sector is specified by virtual track VT and virtual sector VS.

JA9-93-048/jpr

20

Defect table 40 comprises virtual track table (VTT) 42 and virtual sector table (VST) 44. As shown in Fig. 10, virtual sector table 44 stores pseudo LBAs (corresponding to values PLBA in the first embodiment) for a bad sector in an ascending order of absolute block addresses ABA, and virtual track table 42 stores values representing the order where the smallest bad sector belonging to virtual track VT which corresponds to the number of each element is located.

Each item of virtual sector table 44 is two bytes, and the required number of items corresponds to the maximum number of bad sectors which is acceptable for the HDD device. Assuming the maximum number is 1000, virtual sector table 44 requires a storage capacity of 2000 bytes. For example, if the HDD device has a capacity of 500 megabytes, 18 items are sufficient for virtual track table 42 and a storage capacity of 36 bytes is sufficient. Therefore defect table 40 will have a storage capacity of 2036 bytes. On the other hand, if virtual track table 42 and virtual sector table 44 are not used, three bytes are needed for one bad sector. Then defect table 40 requires a storage capacity of 3000 bytes, thus occupying an extra capacity.

Referring now to the flow chart shown in Fig. 11, creation of virtual ID table 38 will be described in detail. Virtual ID table 38 is created by using defect table 40 described above. It is also created for the track where the beginning sector belongs, when a read/write request is issued by other devices such as host computers. Or virtual ID table 38 is created when seek operation transits to the next track after the last sector in the track is processed or read/written.

Upon a read request or write request issued from a host device, or for the logical block address LBA, which is a sector number, being specified as the next track, the virtual track VT and virtual sector VS are specified by using the following equation (4).

$$VT = LBA / NSEC\_VT$$

$$VS = LBA \% NSEC\_VT \dots (4)$$

where NSEC\_VT is the number of sectors per virtual track (= 10000H), and % is an operator for determining the residue of division.

Using a specified virtual track VT and virtual sector VS, a value p which satisfies the following equation (5) is determined at step 304.

JA9-93-048/jpr

21

$$VST[p - 1] \leq VS < VST[p]$$
$$VTT[VT] \leq p < VTT[VT + 1] \dots (5)$$

where  $VST[x]$  is the contents of virtual sector table and  $VTT[x]$  is the contents of virtual track table.

5

The determined value  $p$  corresponds to the number of pseudo LBAs (values PLBA) listed in the defect list  $D\_LST$ . Thus, as in equation (1), adding the value  $p$  to the logical block address LBA to determine the absolute block address ABA (step 306). Next, use the following equation (6) to determine the surface number HD and cylinder number CYL of the magnetic disk which contains the absolute block address ABA at step 308.

10

$$CYL = ABA / (NM\_HD \cdot SCT\_TRK)$$
$$HD = (ABA \% (NM\_HD \cdot SCT\_TRK)) / SCT\_TRK \dots (6)$$

15

where  $NM\_HD$  is the number of heads per track. In equation (6),  $NM\_HD \cdot SCT\_TRK$  may be  $SCT\_CYL$ .

the maximum value  $MAX\_TRK$  and minimum value  $MIN\_TRK$  of the absolute block address ABA for the sector included in the track specified in these magnetic disk surface number and cylinder numbers are determined by using the following equation (7) at step 310, and for the sector included between the determined maximum value  $MAX\_TRK$  and minimum value  $MIN\_TRK$  of the track, a bad sector defined by virtual track table 42 and virtual sector table 44 is extracted at step 312. At this time, if the bad sector exists, the process sets the flag  $DEF\_FL$  (DEFECT FLAG) of virtual ID table 38 which corresponds to the current sector.

20

25

$$MIN\_TRK = (CYL \cdot NM\_HD + HD) \cdot SCT\_TRK$$
$$MAX\_TRK = MIN\_TRK + SCT\_TRK - 1 \dots (7)$$

30

Since the disk rotates constantly and during movement on the track (seek) varies by a predetermined amount (skew) from a straight line in the radial direction, the skew on the target track is calculated at step 314, the physical sector in virtual ID table 38 which corresponds to the skew is used to set the logical block address LBA to increase the logical block address LBA for the next sector at step 316. At this time, the corresponding sector is skipped if the flag  $DEF\_FL$  is set.

35

The initial value of logical block address is  $LBA \cdot MIN\_TRK - m$  ( $m$  is the number of bad sectors which is smaller than the maximum value  $MIN\_TRK$  of the absolute block address ABA for the sector included in the track).

40

JA9-93-048/jpr

22

For skew calculation, a skew table representing the amount of skew per track which is previously recorded is used, along with differences in devices such as drives for each HDD device 10.

5        Processing of read and write operation to the disk using virtual ID table 38 according to the present embodiment will now be described with reference to the flow chart shown in Fig. 12.

10        When the process moves to processing on the logical block address LBA specified by a host device, virtual ID table 38 is referenced to determine a physical sector DT\_SCT which corresponds to the logical block address LBA of the target sector at step 402. Also reference is made to virtual ID table 38 to read a servo number SV\_SCT in the determined physical sector DT\_SCT, and the process waits for the completion of reading by the magnetic head of the servo area 50 being decremented by 1 (SV\_SCT - 1) at step 404. Then a sector pulse signal SP is input and a capacity PTR is set when the end of the servo area 50 decremented by 1 is reached (step 406). Next an instruction for read or write operation is issued to HDC30 at step 408.

20        Whether the target sector exists immediately after the sector pulse signal SP is determined at step 410 by referencing the servo number SV\_SCT in the virtual ID table. If the answer is positive, the flag DNT\_FL is set at step 412. If the answer is negative, the flag DNT\_FL is reset at step 414.

30        This flag DNT\_FL indicates whether the next sector's information is to be read or information is to be written in the next sector. If this flag is being set, read or write operation is made from the beginning of the next sector. If this flag is being reset, the next sector is skipped.

35        The steps described above correspond to steps 202 to 216 in Fig. 7. Reaching the beginning of the sector, a signal is input from HDC30 at step 416 to move the corresponding physical block address in virtual ID table 38 (step 418), and the corresponding information of the moved physical block address in virtual ID table 38 is set in HDC30 for the next sector at step 420.

40        The processing described above corresponds to processing by NSPR62 for referencing pointer table 34 at a predetermined time in an updatable state, to store the next structure information in NSPR62.

JA9-93-048/jpr

23

With reference to virtual ID table 38 being moved, the process determines whether the next sector is a bad sector or not at step 422. If the decision is positive, flag DNT\_FL is reset before step 416 is returned (step 424). If the decision is negative, flag DNT\_FL is set before step 416 is returned (step 426). This processing is repeated until all target sectors are covered (step 428).

In this manner, the present embodiment allows the sector ID to be created by a defect table even with a track where no other sectors are contiguous than those having recorded the data which are not recorded in every sector on the disk, or with a track where a sector is divided by the servo area. Since using a virtual ID table corresponding to the sector ID permits the absolute block address of the disk to be determined, information can be read or written to the sector being requested by a host device without consuming an extra memory elements or capacities.

The table described above may be recorded in the boot track in a predetermined cylinder on the disk, or be stored in ROM provided in the HDD device.

As described above, using HDD device 10 eliminates the need for recording the sector ID. Thus, it is possible to read and write information even when the amount of information increases which can be recorded on the disk.

The magnetic head, as in the aforementioned embodiments, comprises an MR element. It is well known in the art that its writing portion for recording information and reading portion for reading information is offset by a predetermined amount (e.g. several micrometers) toward the radial direction of the disk. Thus, when the magnetic head is so configured that it turns around an axis assumed as an extension to the writing and reading portions for movement (see Fig. 1), this offset will vary in the radial direction with the turn angle. In view of this, in a conventional HDD device, different set positions of the MR element have been used to accommodate both read operation (RD) and write operation (WRT) so that the corresponding magnetic head is positioned immediately above the desired data area. For example, in magnetic head 20A, as shown in Fig. 14, the MR element is so configured that writing element 90 for recording information and reading element 92 for reading information are spaced apart by a predetermined amount. During read operation (RD), magnetic head 20A is located so that reading element 92 is positioned

JA9-93-048/jpr

24

immediately above center line 54A of the track. During write operation (WRT), magnetic head 20A is located so that writing element 90 is positioned immediately above center line 54A of the track.

5 In the prior art HDD device, since the sector ID must be read from the disk, it is necessary for the reading portion to read the sector ID even during write operation (WRT). Thus the conventional magnetic head has been configured so that it can read the sector ID during writing of information (WRT). The length of each head gap has been determined so  
10 that read operation is possible even when the position of the magnetic head is offset from the position specified by a track width TRKw toward the radial direction of the disk. As an indicator which takes into account the relation between this amount of off-track and error rate during read operation, there is OFF TRACK Performance or Error Rate  
15 Bathtub. Using this indicator allows an optimum magnetic head to be configured for the HDD device. Then, when magnetic head 20A regulated by the length of the head gap of read element 92 (referred to as gap length RDw) is located approximately within the width of track 54, the amount of error becomes minimum, and characteristic curve 94 will indicate the  
20 amount of error which linearly increases with the amount of off-track. Therefore, the magnetic head is designed to have a characteristic curve 94 indicating a lower amount of error over a wide range (so-called wider bathtub). Conventionally, in view of this, the length of the head gap of write element 90 (referred to as gap length WTw) has been made longer  
25 than the gap length RDw.

However, since the signal-to-noise ratio is proportional to the gap length RDw, the limit value of gap length RDw is defined to maintain a minimum amount of error. This requires a longer gap length WTw (e.g. 1.0  
30  $\mu\text{m}$ ). However, a longer gap length WTw will increase the track width TRKw. This has precluded improvement of the information recording density in the radial direction of the disk.

HDD device 10 to which the present invention is applicable does not  
35 require any sector ID to be recorded on the disk. Comparing a conventional HDD device with HDD device 10 according to the invention, data is written in the recording area with a predetermined offset in relation to the sector ID recording area for a single sector (see Fig. 13(a)) in the conventional HDD device, while in HDD device 10 according  
40 to the invention, data can be written in aligned recording areas (see Fig. 13(b)). Therefore, the magnetic head design does not require

JA9-93-048/jpr

25

considerations for obtaining a wider bathtub, and the gap length WTw can be specified up to a length approximately conforming to the gap length RDw.

5 The present inventor has found that the information recording density in the radial direction of the disk improves approximately over 10% in HDD device 10 according to the invention in comparison with the prior art HDD device which has a gap length WTw of approximately 1.0  $\mu\text{m}$ , by a magnetic head design with the gap length WTw specified at 0.5  $\mu\text{m}$  or below.

10

As shown in Fig. 16, the servo area 50 includes servo signal 94A and servo signal 94B wherein, for instance, a burst pattern is formed in a staggered fashion in the radial direction of the disk. Normally, to obtain position information from the servo area 50, the read element of the magnetic head is located so that it crosses this staggered servo signal 94 A and servo signal 94B. Thus, with a relative relationship between the gap length RDw of the read element and track width TRKw, detection of the servo signal will decrease with the amount of off-track of the magnetic head, and when the gap length RDw is extremely smaller than the track width TRKw, only a slight off-track makes it impossible to obtain position information. Consequently, positioning accuracy must be higher and in some cases position information cannot be obtained.

25

As above-described, HDD device 10 to which the position invention is applicable does not require the sector ID to be recorded on the disk, thus allowing data to be written in aligned recording areas (see Fig. 13(b)). Therefore, as a condition of the magnetic head which is required for obtaining position information from the servo area 50, only an offset in spacing between the read and write elements during turning of arms should be considered. It is not necessary to consider the amount of off-track caused by specifying the magnetic head at different positions during read and write operation. Then, the gap length RDw can be specified up to a length approximately conforming to the track width TRKw. This will provide an increased track density in the radial direction of the disk for HDD device 10 according to the present invention.

30

As described above, by using the information recording disk in accordance with the present invention, information such as the structure of each sector can be referenced and the sector structure can readily be recognized even when data-only sectors are adjacent or a sector crosses

40

JA9-93-048/jpr

26

the servo area. Thus, the present invention offers the advantage of an increased amount of information which can be recorded in the information recording disk.

5 Moreover, by using the disk drive system according to the present invention, read and write operation can be performed efficiently with less resources since storage means such as registers store the structure and operation of the current and next sectors.

10 A further advantage of the present invention is that more information can be handled without consuming extra storage on the hard disk drive device or information recording disk, since a requested sector can be determined by using a virtual ID table created with a bad sector table concerning any bad sector on the information recording disk.

15 A still another advantage offered by the present invention is that the track density in the radial direction of the disk can be increased by configuring the head gap length of the read portion to be approximately equal to the head gap length of the write portion or designing the head  
20 gap of the read portion to have substantially the same dimension with the track width.



JA9-93-048/jpr

27

CLAIMS

1. A information recording disk comprising:

5 at least one servo area which stores position information for identifying the track position;

at least one track wherein an area without said servo area is divided by a plurality of sectors, which includes at least one sector which crosses said servo area, each of said plurality of sectors having the same  
10 capacity; and

a table representing the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing  
15 said servo area, said capacity covering up to the crossing position, for uniquely identifying each position of a plurality of sectors.

2. A information recording disk comprising:

20 at least one servo area which stores position information for identifying the track position;

at least one track wherein an area without said servo area is divided by a plurality of sectors, which includes at least one sector crossing said  
25 servo area, each of said plurality of sectors having the same capacity;

a table representing the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing  
30 said servo area, said capacity covering up to the crossing position, for uniquely identifying each position of a plurality of sectors; and

a list storage means for successively storing as a pseudo logical sector identifier a logical sector identifier which should be given to a bad  
35 sector when successively specifying a logical sector identifier for identifying each sector other than any bad sector contained in said track.

3. A disk drive system comprising:

40

JA9-93-048/jpr

28

an information recording disk having at least one track divided by at least one servo area storing position information for identifying the track position and wherein an area without said servo area is divided so that sectors having the same capacities are successively located;

5

a magnetic head for reading and writing information in said information recording disk;

10

storage means consisting of a first storage means for storing the current sector's structure, a second storage means for storing the next sector's structure, and a third storage means for storing the current sector's operation;

15

a table storing the structure of each sector which represents the relationship among a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, and the capacity of the sector crossing said servo area, said capacity covering up to the crossing position, for uniquely identifying each position of a plurality of sectors;

20

a list storage means for successively storing as a pseudo logical sector identifier a logical sector identifier which should be given to a bad sector when successively specifying a logical sector identifier for identifying each sector other than any bad sector contained in said track;

25

means for calculating the physical sector position by referencing said list storage means to read the number of logical sector position identifiers which is equal to or smaller than requested logical sector position identifiers, and adding the number being read to the requested logical sector position identifiers to calculate physical sector position identifiers for the physical sectors corresponding to the requested logical sector identifiers;

30

means for processing sectors in accordance with the current sector's structure stored in said first storage means and the current sector's operation stored in said third storage means;

35

means for identifying the beginning of a sector based on the current sector's structure stored in said first storage means after identifying the end of said servo area by using an output signal from said magnetic head; and

40

JA9-93-048/jpr

29

controller means exercising control when said beginning of the sector is identified, so that said first storage means stores the next sector's structure stored in said second storage means and said third storage means stores the next sector's operation stored in a fourth storage means, and that said second storage means stores the structure of the next sector including the physical sector position identifier calculated by said physical sector position calculating means by referencing said table during processing by said processing means and said fourth storage means stores the next sector's operation.

4. A disk drive system comprising:

said information recording disk according to claim 2;

a magnetic disk for reading and writing information in said information recording disk;

storage means consisting of a first storage means for storing the current sector's structure, a second storage means for storing the next sector's structure, a third storage means for storing the current sector's operation, and a fourth storage means for storing the next sector's operation;

means for calculating the physical sector position by referencing said list storage means to read the number of logical sector position identifiers which is equal to or smaller than requested logical sector position identifiers, and adding the number being read to the requested logical sector position identifiers to calculate physical sector position identifiers for the physical sectors corresponding to the requested logical sector identifiers;

means for processing sectors in accordance with the current sector's structure stored in said first storage means and the current sector's operation stored in said third storage means;

means for identifying the beginning of a sector based on the current sector's structure stored in said first storage means after identifying the end of said servo area by using an output signal from said magnetic head; and

JA9-93-048/jpr

30

controller means exercising control when said beginning of the sector is identified, so that said first storage means stores the next sector's structure stored in said second storage means and said third storage means stores the next sector's operation stored in said fourth storage means, and that said second storage means stores the structure of the next sector including the physical sector position identifier calculated by said physical sector position calculating means by referencing said table during processing by said processing means and said fourth storage means stores the next sector's operation.

5. A disk drive system comprising:

said information recording disk according to claim 1;

a magnetic disk for reading and writing information in said information recording disk;

means for creating a bad sector table when a virtual sector and virtual track each of which having a predetermined capacity are assumed and a physical sector identifier representing the position of each sector other than any bad sector which is included in said track is successively specified as a logical sector identifier, said bad sector table consisting of a virtual sector table wherein a physical sector identifier which should be given to the position of any bad sector is successively stored as a pseudo logical sector identifier and a virtual track table for storing a pseudo logical sector identifier for any bad sector which corresponds to the smallest physical sector identifier for the same track which is contained in said virtual sector table;

means for creating a virtual ID table by using said table and said bad sector table, said virtual ID table representing the structure of each virtual sector in a virtual track which consists of a physical sector identifier for identifying each sector on said divided track based on said servo area, said position information, the capacity of the sector crossing the said servo area which covers up to the crossing position, and a logical sector identifier; and

controller means for exercising control to determine the virtual track and virtual sector which correspond to the position identifier for a requested logical sector by referencing said virtual ID table and

JA9-93-048/jpr

31

determine a corresponding physical sector in the determined virtual track and virtual sector.

5 6. The disk drive system according to any one of claims 3 to 5,  
characterized in that said magnetic head consists of a recording portion  
for recording information in said information recording disk and a  
reading portion spaced apart by a predetermined amount from said  
recording portion for reading information from said information recording  
10 disk, and the length of the head gap of said reading portion is  
configured so as to substantially conforms to the length of the head gap  
of said recording portion.

15 7. The disk drive system according to any one of claims 3 to 5,  
characterized in that said magnetic head consists of a recording portion  
for recording information in said information recording disk and a  
reading portion spaced apart by a predetermined amount from said  
recording portion for reading information from said information recording  
disk, and the length of the head gap of said reading portion is  
20 configured so as to substantially conforms to the width of said track.

<b>Patents Act 1977</b> <b>Examiner's report to the Comptroller under Section 17</b> <b>(The Search report)</b>	<b>Application number</b> <b>GB 9425465.3</b>
<b>Relevant Technical Fields</b>  (i) UK Cl (Ed.N)      G5R (RHE, RHX, RB26) (ii) Int Cl (Ed.6)      G11B 5/012, 5/55, 7/007, 20/12, 20/18, 27/10	<b>Search Examiner</b> <b>P R SLATER</b>
<b>Databases (see below)</b> (i) UK Patent Office collections of GB, EP, WO and US patent specifications.  (ii) ONLINE DATABASES: WPI, INSPEC	<b>Date of completion of Search</b> <b>22 MARCH 1995</b>  <b>Documents considered relevant following a search in respect of Claims :-</b> <b>1-7</b>

**Categories of documents**

<b>X:</b> Document indicating lack of novelty or of inventive step.	<b>P:</b> Document published on or after the declared priority date but before the filing date of the present application.
<b>Y:</b> Document indicating lack of inventive step if combined with one or more other documents of the same category.	<b>E:</b> Patent document published on or after, but with priority date earlier than, the filing date of the present application.
<b>A:</b> Document indicating technological background and/or state of the art.	<b>&amp;:</b> Member of the same patent family; corresponding document.

Category	Identity of document and relevant passages	Relevant to claim(s)
A	EP 0522750 A2 (IBM) see whole document	1, 2, 3

**Databases:** The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).